



SS54A 40VRRM SBD Surface Mount Schottky Barrier Rectifiers DO-214AC SMA Package

Our Product Introduction

Basic Information

- Place of Origin: Shenzhen, Guangdong, China
- Brand Name: SOCAY
- Certification: REACH, RoHS, ISO
- Model Number: SS54A
- Minimum Order Quantity: 5000PCS
- Price: Negotiable
- Delivery Time: 5-8 work days



Product Specification

- Electronic Component Name: Schottky Barrier Rectifiers
- Rectifiers Package: DO-214AC(SMA)
- Max. VRRM: 40V
- Rectifiers Max. VRMS: 28V
- SBD Max. VDC: 40V
- Max. Average Forward Rectified Current: 5A
- Rectifiers IFSM: 150A
- Rectifiers VF: 0.55V
- Highlight: **SS54A Schottky Barrier Rectifiers,
Surface Mount Schottky Barrier Rectifiers,
SMA Package Schottky Barrier Rectifiers**



for more products please visit us on socaydiode.com

Product Description

SS54A 40VRRM SBD Surface Mount Schottky Barrier Rectifiers DO-214AC(SMA) Package

Schottky Barrier Rectifiers DATASHEET: [SS54A~SS520A\(SMA\)_v2307.1.pdf](#)

Schottky Barrier Rectifiers SS54A Features:

Metal silicon junction, majority carrier conduction

Suitable for surface mounted applications

Merit: Low power loss, high efficiency

Merit: High forward surge current capability

For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.

Schottky Barrier Rectifiers SS54A Mechanical Data:

Schottky Barrier Rectifiers SS54A Case: SMA.

SS54A Terminals: Solderable per MIL-STD-750, Method 2026.

Approx. Weight: 60mg / 0.0021oz.

Schottky Barrier Rectifiers SS54A Max. Ratings & Thermal Characteristics:

Schottky Barrier Rectifiers' ratings at 25 ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %.

Parameter		Symbol	SS54A	SS56A	SS510A	SS515A	SS520A	Unit
Rectifiers Maximum Repetitive Peak Reverse Voltage		VRRM	40	60	100	150	200	V
Rectifiers Maximum RMS Voltage		VRMS	28	42	70	105	140	V
Rectifiers Maximum DC Blocking Voltage		VDC	40	60	100	150	200	V
Maximum Average Forward Current		IF(AV)	5.0					A
Rectifiers Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)		IFSM	150					A
Rectifiers Max Instantaneous Forward Voltage at 5 A		VF	0.55	0.70	0.85	V		
Maximum DC Reverse Current at Rated DC Reverse Voltage	Ta=25	IR	1.0					mA
			50					
	Ta=100							
Rectifiers Typical Junction Capacitance(1)		Cj	500	300	pF			
Typical Thermal Resistance(2)		RθJA	60					/W
Operating Junction Temperature Range		TJ	-55 to +150					
Rectifiers Storage Temperature Range		TSTG	-55 to +150					

Notes: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

Schottky Barrier Rectifiers SS54A Dimensions:

DO-214AC (SMA)		Dimensions			
Dim		Inches		Millimeters	
		Min	Max	Min	Max
A		0.067	0.093	1.7	2.36
B		0.049	0.067	1.25	1.7
C		0.002	0.008	0.05	0.2
D		--	0.02	--	0.51
E		0.03	0.06	0.76	1.52
G		0.185	0.209	4.7	5.31
H		0.157	0.185	4	4.7
J		0.086	0.11	2.18	2.8

Schottky Barrier Rectifiers SS54A Packaging Information:

Part Number	Component Package	Quantity
SS54A~SS520A	DO-214AC(SMA)	5000 PCS

Schottky Barrier Rectifiers Warning:

SOCAY owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property.

SOCAY reserves the right to make changes without further notice to any products herein.

SOCAY makes no warranties, representations or warranties as to the fitness of its products for any particular purpose, and disclaims any liability.

The parameters provided in the SOCAY datasheet specification may vary from application to application, and the actual performance may vary over time. All operating parameters must be verified by the customer's technical expert before application.

Any and all responsibilities and liabilities are disclaimed if any item under this notice of warning is not complied with.



Shenzhen Socay Electronics Co., Ltd.



+8618126201429



sylvia@socay.com



socaydiode.com

4/F, Block C, HeHengXing Science & Technology Park, 19 MinQing Road, LongHua District, Shenzhen City,
GuangDong Province, China